



BOM LEGEND	
	SECONDARY BUS
	CONDUCTOR SIZE & TYPE
A	266.8 kcmil AL
B	#3/0 AL
C	#4 AL

BILL OF MATERIALS FOR 30-3600						
ITEM NO.	DESCRIPTION	ITEM I.D.	QUANTITY			
			A	B	C	
1	CONNECTOR MINI WEDGE 266.8 kcmil TO #12	7231210	1	-	-	
2	CONNECTOR MINI WEDGE #3/0 TO #12 OR #14	9656247	2	3	-	
3	CONNECTOR MINI WEDGE #4 TO #12 OR #14	7231050	-	-	3	
4	FUSE 600 V 10 A 100 kA FAST-ACTING	7020006	1	1	1	
5	FUSEHOLDER 600 V 30 A WATERTIGHT	7030139	1	1	1	
6	CABLE 2C #12 SOL CU WITH #14 SOL CU BARE GND	7155155	3	3	3	
OPEN BIN MATERIALS						
7	COVER PLASTIC FOR MINI WEDGE CONNECTORS	7231375	3	3	3	

- NOTES:**
- REFER TO STD. 30-3200 FOR FUSE ASSEMBLY INSTALLATION DETAIL.
 - WHEN CONNECTING CU TO AL USING MINI WEDGE CONNECTORS, PLACE CU CONDUCTOR BELOW AL CONDUCTOR IN ORDER TO PREVENT GALVANIC CORROSION.

DISTRIBUTION CONSTRUCTION STANDARD
Street Lighting

**OVERHEAD 120 V SUPPLY
TO POLE-MOUNTED LUMINAIRE**



Approved By:
E.H. 2016-07-28

Drafted By:
B.W.

Designed By:
E.H.

Original Issue:

Scale:
N.T.S.

Rev:

0

30-3600

1/1